# **Marine Physical Laboratory**

# **Acoustic Array Hardware Development** and Bottom Reverberation Experiment

W. S. Hodgkiss

Supported by the Chief of Naval Research Grant N00014-90-J-4042

# **Final Report**

MPL-U-69/95 September 1995

Approved for public release; distribution is unlimited.





University of California, San Diego Scripps Institution of Oceanography

## REPORT DOCUMENTATION PAGE Form Approved OMB No. 0704-0188 Public reporing burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data need ed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503. 2. Report Date. September 1995 3. Report Type and Dates Covered. 1. Agency Use Only (Leave Blank). Final Report 5. Funding Numbers. 4. Title and Subtitle. N00014-90-J-4042 Acoustic Array Hardware Development and Bottom Reverberation 6. Author(s). Project No. W. S. Hodgkiss Task No. 8. Performing Organization 7. Performing Monitoring Agency Names(s) and Address(es). Report Number. University of California, San Diego MPL-U-69/95 Marine Physical Laboratory Scripps Institution of Oceanography San Diego, California 92152 9. Sponsoring/Monitoring Agency Name(s) and Address(es). 10. Sponsoring/Monitoring Agency Report Number. Chief of Naval Research Department of the Navy 800 North Quincy Street Arlington, VA 22217-5660 Code 321OA 11. Supplementary Notes. 12b. Distribution Code. 12a, Distribution/Availability Statement. Approved for public release; distribution is unlimited. 13. Abstract (Maximum 200 words). Four 64-element, large dynamic range, acoustic arrays and autonomous recording capsules were designed and fabricated for deployment in the major bottom acoustics experiment of the ONR Acoustic Reverberation Special Research Program (ARSRP). Subsequently, these arrays and recording capsules were taken to sea and recorded bistatic scatter during the July 1993 bottom reverberation experiment. 15. Number of Pages. 14. Subject Terms. acoustic arrays, autonomous recording capsules, bottom reverberation 16. Price Code.

19. Security Classification

Unclassified

of Abstract..

20. Limitation of Abstract.

None

17. Security Classification of Report.

Unclassified

18. Security Classification

Unclassified

of This Page.

# Acoustic Array Hardware Development and Bottom Reverberation Experiment

William S. Hodgkiss

Final Report to the Office of Naval Research Grant N00014-90-J-4042 for the Period 7-1-90 - 1-31-94

#### Abstract

Four 64-element, large dynamic range, acoustic arrays and autonomous recording capsules were designed and fabricated for deployment in the major bottom acoustics experiment of the ONR Acoustic Reverberation Special Research Program (ARSRP). Subsequently, these arrays and recording capsules were taken to sea and recorded bistatic scatter during the July 1993 bottom reverberation experiment.

### Research Objective

The objective of this project was to develop four 64-element, acoustic arrays and autonomous recording capsules and to deploy these sensor systems during the July 1993 ONR ARSRP bottom reverberation experiment.

### Research Summary

Each of the four reverberation arrays consists of 64 hydrophone elements with 1.875 m interelement spacing ( $\lambda/2$  at 400 Hz). The time series from the array elements is sampled at  $f_s = 1.5$  kHz using 24 bit A/D converters

#### **Research Summary**

and multiplexed onto a single digital data stream for transmission to the data recording package. In addition, there are 16 navigation receivers embedded in each array for localizing the array elements. These navigation receivers detect transponder arrivals in the 7.5-14.5 kHz band. A more detailed discussion of the hardware design is contained in [1].

Each of the four autonomous recording packages makes use of a 24" diameter aluminum pressure vessel as the primary electronics housing. The array digital data stream will be recorded on an Exabyte-8500 8 mm cassette recorder (5 GB/tape). The capability of recording several of these tapes is provided by an Exabyte 10 cassette stacker to provide a total storage capacity of 50 GB. Real-time management of the array data and stacker is provided by a CMOS 68000 CPU. In addition, the CPU interrogates a transponder net for array element localization purposes.

The ARSRP bottom reverberation experiment was carried out in the vicinity of the Mid-Atlantic Ridge in July 1993. Three ships participated in the experiment - the M/V Cory Chouest, the R/V Alliance, and the R/V Knorr. W. Hodgkiss was Chief Scientist on the R/V Knorr as well as Chair of the Acoustics Experiment Working Group which planned the experiment. The Cory Chouest deployed a vertical line source array and a horizontal line receive array, the Alliance deployed a flextensional source and a horizontal line receive array, and the Knorr deployed both the vertical, near-bottom reverberation arrays and recording packages as well as the DTAGS (Deeply Towed Acoustics Geophysics System).

The bottom reverberation experiment was very successful and all three ships collected a substantial amount of both monostatic and bistatic reverberation data. An intercomparison of the autonomous vertical line array and DTAGS data is contained in [2,3]. The activities of the R/V Knorr during the 7 July - 2 August 1993 sea trip are documented in a trip report [4]. Lastly, a quick-look analysis of the data quality across the entire data set recorded by the vertical arrays is documented in [5].

#### References

- 1. W.S. Hodgkiss, J. C. Nickles, G.L. Edmonds, R.A. Harriss, and G.L. D'Spain, "A large dynamic range vertical array of acoustic sensors," appears in: O. Diachok, A. Caiti, P. Gerstoft, and H. Schmidt (Eds). *Full Field Inversion Methods in Ocean and Seismic Acoustics*. (Kluwer Academic Publishers, The Netherlands, 1995), pp. 205-210.
- 2. W.S. Hodgkiss and J.F. Gettrust, "VLA/GARRP and DTAGS Shipboard Data Intercomparison (Site A)" (July 1993).
- 3. W.S. Hodgkiss and J.F. Gettrust, "VLA/GARRP and DTAGS Shipboard Data Intercomparison (SedScatt)" (August 1993).
- 4. W. S. Hodgkiss, "ONR ARSPP Acoustics Experiment R/V KNORR," MPL TM-441 (January 1994).
- 5. L.P. Berger, "ARSRP Experiment: Vertical Array Quick-Look Analysis," MPL-U-77/93 (December 1993).

#### **ONR/MPL REPORT DISTRIBUTION**

Chief of Naval Research
Department of the Navy
Ballston Tower One
800 North Quincy Street
Arlington, VA 22217-5660
Atten:c Dr. Richard Doolittle
Code 321OA

Department of the Navy
Office of Naval Research
San Diego Regional Office
4520 Executive Drive, Suite 300
San Diego, CA 92121-3019

Commanding Officer (1)
Naval Research Laboratory
Atten: Code 2627
Washington, D.C. 20375-5320

Defense Technical Information Center
Building 5, Cameron Station
Alexandria, VA 22304-6145